

# MET-A-SIL WATERPROOFING

The coverage rates listed on this page are estimates based on typical conditions. It is critical to check all fasteners before adding mastic to ensure they are tight. Add stitch screws at seams before applying mastic when necessary. The width of the detail may need to be wider than estimated.



MATERIAL	COVERAGE PER GALLON	WIDTH	WET MILS	AVERAGE DRY MILS	COVERAGE PER 5 GALLON PAIL
----------	---------------------	-------	----------	------------------	----------------------------

### VERTICAL SEAMS

Urethane Brush Grade 522	250 linear ft./ gallon	2" wide	35	25	1250 linear feet/pail
--------------------------	------------------------	---------	----	----	-----------------------

### HORIZONTAL SEAMS, RAKES

Urethane Brush Grade 522	75 linear ft. / gallon	4" wide	42	30	375 linear feet/ pail
--------------------------	------------------------	---------	----	----	-----------------------

### FLASHINGS

Urethane Brush Grade 522	50 linear ft. / gallon	6" wide	70	50	250 linear feet/ pail
--------------------------	------------------------	---------	----	----	-----------------------

### FASTENERS

Urethane Brush Grade 522	On average we have found coverage on a standard R panel to be 800 sq. ft. per gallon will cover the fasteners.				
--------------------------	----------------------------------------------------------------------------------------------------------------	--	--	--	--