

## Product Detail Report

Company: American Weatherstar

Trade Name: AWS Urethane Brush-Grade 522 (Maintenance Coating)

Country: United States of America

Document Link: (none)

Assemblies: 0

Comments: AWS Urethane Brush-Grade 522 is a moisture cure polyurethane elastomeric sealant. It is Approved as surface treatment for modified bitumen roof covering systems, for use with American Weatherstar Ure-A-Sil System. Application of the coating system will not increase the fire, wind, or hail resistance performance of the existing roof. Prior to application of the base coat - all gaps, voids, and uneven surfaces of the underlying modified bitumen roof covering system are prepared by filling the gaps and transitional surfaces with AWS Urethane Brush-Grade 522 brush applied at maximum thickness of 32 wet mils and allowed to dry, per the manufacturer's specifications. Subsequently, 3 in (76 mm) wide strips of AWS Non-Woven Fabric are laid over the prepared areas and are set with AWS Urethane Brush-Grade 522 spray or roller applied to the top surface of the Approved modified bitumen roof covering system at a rate of 1.5 gal/square (0.61 L/m<sup>2</sup>).

## **Approved Uses :**

### **Maintenance Coating**

Material: Polyurethane

Substrates Used With: Mod Bit Roof

Assemblies: 0

Comments: none