TERMINATOR 622

DESCRIPTION

Terminator 622 is a technologically-advanced, 100% solids, moisture-cure sealant/adhesive. This high-strength versatile product has excellent elasticity and adhesion, making it ideal for repairs. Designed for industrial use, it can be applied to most surfaces even when the area is wet. Not only is it waterproof, it is also UV stable, for up to 5 years, and low VOC.

ADVANTAGES

- Self-leveling technology for all seams, fasteners, ridge caps, flashings, and penetrations
- Moisture-curing, multi-purpose, one-component sealant/adhesive
- Designed for industrial uses requiring elasticity, high strength, and excellent adhesion
- May be applied to surfaces at or below freezing temperatures—make all attempts to remove frost
- Performance at temperatures as low as -40° F
- Bonds to damp surfaces and is rain tolerant during cure
- Cures to a waterproof tough flexible sealant
- Low odor and minimal shrinkage
- Non-staining and mildew resistant
- UV resistant
- VOC compliant

BASIC USES

Industrial uses requiring high elasticity, high strength, and outstanding adhesion for a wide-range of substrates. Terminator 622 bonds aggressively to steel, aluminum, modified bitumen, built-up roofing, spray foam, styrofoam, eps, glass, wood, fiberglass, concrete, and coated metals.

INSTALLATION

- **Surface Prep:** All surfaces must be cleaned properly. Any existing coating must be checked for good adhesion. Before application, any loosely adhered coating must be removed and bare surfaces must be prepared, cleaned and checked for compatibility.
- **Brush:** High-quality synthetic bristle brush
- **Caulk Gun:** 28 fl. oz. cartridges

WARRANTY

American WeatherStar warrants that the material supplied will meet or exceed physical properties as published. The contractor guarantees that workmanship will be free of defects in coating application. Since performance of previously installed substrate is beyond the control of American WeatherStar or the contractor, requests for additional warranty coverage shall be subject to prior approval by American WeatherStar.

TECHNICAL DATA

SOLIDS BY VOLUME:	100%
ELONGATION:	500%
TENSILE STRENGTH:	200 psi
FLASH POINT:	N/A
HARDNESS:	25 (5 day ambient cure)
MINIMUM APPLICATION TEMP.:	32°F
DRY TIME:	2–12 hours
SERVICE TEMPERATURE:	-40° to 200°F
LOW TEMP FLEX:	-20°F
SLUMP:	Some self-leveling
COLOR:	White
PACKAGING:	10.3 oz tube, 2-gallon pail

SAFETY INFORMATION

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

AMERICAN WEATHERSTAR LLC
8095 Padgett Switch Rd. | Irvington, AL 36544 | USA
www.americanweatherstar.com | info@americanweatherstar.com
Toll Free: 800-771-6643 | Fax: 251-479-3602