

The coverage rates listed on this page are estimates based on typical conditions. It is critical to check all fasteners before adding mastic to ensure they are tight. Add stitch screws at seams before applying mastic when necessary. The width of the detail may need to be wider than estimated.



| MATERIAL | COVERAGE/GALLON | WIDTH | WET MILS | AVERAGE DFT | COVERAGE/5-GALLON PAIL |
|----------|-----------------|-------|----------|-------------|------------------------|
|----------|-----------------|-------|----------|-------------|------------------------|

SEAMS & TERMINATIONS

| | | | | | |
|--------------------------|-----------------------|----|----|----|-------------------------------------|
| Silicone Brush-Grade 422 | 200 linear ft./gallon | 3" | 33 | 30 | 1,000 linear ft./pail |
| Terminator 622 | 200 linear ft./gallon | 3" | 30 | 30 | 300 linear ft./pail (2-gallon pail) |

FLASHINGS, PENETRATIONS, CURBS, DRAINS, CORNERS, & SCUPPERS

| | | | | | |
|--------------------------|----------------------|----|----|----|-------------------------------------|
| Silicone Brush-Grade 422 | 50 linear ft./gallon | 6" | 65 | 60 | 250 linear ft./pail |
| Terminator 622 | 50 linear ft./gallon | 6" | 60 | 60 | 100 linear ft./pail (2-gallon pail) |

