



# ACRYLIC SKYLIGHT SEALER 230

## DESCRIPTION

Acrylic Skylight Sealer 230 elastomeric coating is a translucent gloss used for sealing skylights.

## ADVANTAGES

- Extremely tough, durable, UV resistant protective sealant
- Excellent water resistance
- Good bridging qualities over hairline cracks and small openings
- Excellent adhesion and binding qualities
- Outstanding resistance to dirt collection and pollutants
- Keeps surface clear thereby reducing maintenance costs
- Environmentally safe

## BASIC USES

Acrylic Skylight Sealer 230 is used with the American WeatherStar metal roof coating system to help seal and recondition skylights. Note, if skylights are cracked, the Acrylic Skylight Sealer 230 is not sufficient. In this case the skylight should be replaced.

## INSTALLATION

All surfaces to be coated must be cleaned properly. Power washing is recommended. Any existing coating must be checked for good adhesion. Before application, any loosely adhered coating must be removed and bare surfaces must be prepared, cleaned and checked for compatibility.

This product is ready to use. Thinning is not required or recommended.

- Spray: Airless Sprayer, 1/2 gpm capacity with a #517 tip.
- Brush: High-quality synthetic bristle brush.
- Roller: Long nap roller.

## APPLICATION TEMPERATURES

Min Ambient: 50°F (10°C)  
 Max Ambient: 110°F (43.3°C)  
 Min Surface: 50°F (10°C)  
 Max Surface: 130°F (54.4°C)

Minimum temperatures must be rising following applications. Contact technical services for more information.

### Do not apply when:

- Dew point is within 5°F (2.77°C) of ambient temperatures
- Precipitation, fog, or dew is imminent prior to cure of the product
- Freezing temperatures are expected prior to cure of the product

## TECHNICAL DATA

SOLIDS BY VOLUME:	45% ± 2%
VISCOSITY:	3000 CPS
WEIGHT:	8.7 lbs. per gallon
FLASH POINT:	NA
HARDNESS, SHORE A:	60
MINIMUM APPLICATION TEMP:	50°F
DRYING TIME:	2-12 hours
SERVICE TEMPERATURE:	-40°F to 200°F
COLOR:	Translucent
PACKAGING:	5 gallon

## SAFETY INFORMATION

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

## AMERICAN WEATHERSTAR LLC

8095 Padgett Switch Rd. | Irvington, AL 36544 | USA  
[www.americanweatherstar.com](http://www.americanweatherstar.com) | [info@americanweatherstar.com](mailto:info@americanweatherstar.com)  
 Toll Free: 800-771-6643 | Fax: 251-479-3602