



WALK PATH GRANULES 1100

DESCRIPTION

Walk Path Granules 1100 were designed to enhance the impact resistance of the roof surface and also provide a non-skid walking surface when embedded in Silicone Walk Path 415. They have also been designed to provide high-performance UV resistance for outdoor applications. Only the most UV stable pigments have been incorporated into the product to maintain colorfastness.

INSTALLATION

Immediately after the application of Silicone Walk Path 415, evenly broadcast the Walk Path Granules 1100 into the wet coating. The recommended application rate is as follows:

- **Walkway Areas:** 25 mils (1.65gal/sq.) of Silicone Walk Path 415 with 40 lbs./sq. of Walk Path Granules 1100
- **Impact Resistant Areas:** 40 mils (2.65 gal/sq.) of Silicone Walk Path 415 with 60 lbs./sq. of Walk Path Granules 1100

IMPORTANT: Walk Path Granules 1100 will settle into the Silicone Walk Path 415 coating. Apply the granules generously, and within a few minutes inspect the surface and re-apply as needed to obtain a continuous film of granules.

STORAGE AND SHELF LIFE

Walk Path Granules 1100 have a recommended shelf life of five (5) years when stored in dry environments.

WARRANTY

American WeatherStar warrants that the material supplied will meet or exceed physical properties as published. The contractor guarantees that workmanship will be free of defects in coating application. Since performance of previously installed substrate is beyond the control of American WeatherStar or the contractor, requests for additional warranty coverage shall be subject to prior approval by American WeatherStar.

TECHNICAL DATA

HARDNESS:	6.5-7.0
BULK DENSITY:	90-100 Lbs./Cu. Ft. (ASTM C29/C29M-97)
SPECIFIC GRAVITY:	2.65 (ASTM C128-01e1)
COLOR:	Bright Yellow
PACKAGING:	Packaged in two (2) gallon pails containing 25 lbs. of product.

SAFETY INFORMATION

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

AMERICAN WEATHERSTAR LLC

8095 Padgett Switch Rd. | Irvington, AL 36544 | USA
www.americanweatherstar.com | info@americanweatherstar.com
 Toll Free: 800-771-6643 | Fax: 251-479-3602