

SECTION 1: Identification**1.1. Product identifier****Product Identity**

AWS Butyl Brush-Grade 320

Alternate Names

AWS Butyl Brush-Grade 320

1.2. Relevant identified uses of the substance or mixture and uses advised against**Intended use**

Butyl Rubber Roof Coating.

Application Method

See Technical Data Sheet.

1.3. Details of the supplier of the safety data sheet**Company Name**American WeatherStar, LLC.
3100 Lees Lane
Mobile, AL 36693**Emergency****24 hour Emergency Telephone No.**

INFOTRAC— (800) 535-5053

Customer Service: American WeatherStar, LLC.

800-771-6643

SECTION 2: Hazard(s) Identification**2.1 Classification of the substance or mixture**

Flam. Liq. 2;H225	Highly Flammable liquid and vapor.
Skin Irrit. 2;H315	Causes skin irritation.
Eye Irrit. 2;H319	Causes serious eye irritation.
Skin Sens. 1;H317	May cause an allergic skin reaction.
Aquatic Chronic 2;H411	Toxic to aquatic life with long lasting effects.

2.2 Label elements

Using the Toxicity Data listen in section 11 and 12 the product is labeled as follows.

**Danger**

H225 Highly flammable liquid and vapor.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H411 Toxic to aquatic life with long lasting effects.

[Prevention]:

- P210 Keep away from heat / sparks / open flames / hot surfaces - No smoking.
- P235 Keep cool.
- P240 Ground / bond container and receiving equipment.
- P241 Use explosion-proof electrical / ventilating / light / equipment.
- P242 Use only non-sparking tools.
- P243 Take precautionary measures against static discharge.
- P261 Avoid breathing dust / fume / gas / mist / vapors / spray.
- P262 Do not get in eyes, on skin, or on clothing.
- P264 Wash thoroughly after handling.
- P272 Contaminated work clothing should not be allowed out of the workplace.
- P273 Avoid release to the environment.
- P280 Wear protective gloves / eye protection / face protection.

[Response]:

- P301+310 IF SWALLOWED: Immediately call a POISON CENTER or doctor / physician.
- P302+352 IF ON SKIN: Wash with plenty of soap and water.
- P303+361+353 IF ON SKIN (or hair): Remove / Take off immediately all contaminated clothing. Rinse skin with water / shower.
- P305+351+338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.
- P313 Get medical advice / attention.
- P321 Specific treatment (see information on this label).
- P331 Do NOT induce vomiting.
- P333+313 If skin irritation or a rash occurs: Get medical advice / attention.
- P337+313 If eye irritation persists: Get medical advice / attention.
- P362 Take off contaminated clothing and wash before reuse.
- P363 Wash contaminated clothing before reuse.
- P370+378 In case of fire: Use extinguishing media listed in section 5 of SDS for extinction.
- P391 Collect spillage.

[Storage]:

- P403+233 Store in a well ventilated place. Keep container tightly closed.

[Disposal]:

- P501 Dispose of contents / container in accordance with local / national regulations.

SECTION 3: Composition/Information on Ingredients

This product contains the following substances that present a hazard within the meaning of the relevant State and Federal Hazardous Substances regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Aliphatic Hydrocarbon CAS Number: 0064742-49-0	25 - 50	Asp. Tox. 1;H304	[1]
Petroleum Resin CAS Number: 0064742-16-1	10 - 25	Not Classified	[1]

Polybutene CAS Number: 0009003-29-6	1.0 - 10	Not Classified	[1]
Titanium dioxide CAS Number: 0013463-67-7	1.0 - 10	Not Classified	[1][2]
BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE, HYD CAS Number: 0066070-58-4	1.0 - 10	Aquatic Chronic 4;H413	[1]
Alkyl quaternary ammonium bentonite CAS Number: 0068953-58-2	1.0 - 10	Not Classified	[1]
Calcium carbonate CAS Number: 0001317-65-3	1.0 - 10	Not Classified	[1][2]
Xylene CAS Number: 0001330-20-7	1.0 - 10	Flam. Liq. 3;H226 Acute Tox. 4;H332 Acute Tox. 4;H312 Skin Irrit. 2;H315	[1][2]
2-N-octyl-4-isothiazoline-3-one CAS Number: 0026530-20-1	0.10 - 1.0	Acute Tox. 3;H331 Acute Tox. 3;H311 Acute Tox. 4;H302 Skin Corr. 1B;H314 Skin Sens. 1;H317 (@>0.05%) Aquatic Acute 1;H400 Aquatic Chronic 1;H410	[1]

In accordance with paragraph (i) of §1910.1200, the specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

[1] Substance classified with a health or environmental hazard.

[2] Substance with a workplace exposure limit.

[3] PBT-substance or vPvB-substance.

*The full texts of the phrases are shown in Section 16.

SECTION 4: First Aid Measures

4.1 Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Flush with water and remove contact lenses. Continue to flush eyes with large amounts of water for 15 minutes. Get medical attention immediately.
Skin	Remove contaminated clothing and shoes/boots. Wash affected area with large amounts of soap and water. Get medical attention immediately.
Ingestion	If swallowed do not give anything to drink. Do not induce vomiting except under physician's instruction. Get medical attention immediately. Never give anything by mouth to an unconscious person.

4.2 Most important symptoms and effects, both acute and delayed

Overview Effects of Overexposure

Inhalation: Breathing large amounts of vapors or mists may be harmful. Symptoms include central nervous system excitement (giddiness, liveliness) followed by central nervous system depression (fatigue, dizziness, drowsiness, nausea, headache). Prolonged

exposure may cause liver and kidney damage.

Eyes: May cause mild eye irritation such as stinging, redness, & tearing.

Skin: May be absorbed through the skin and cause skin irritation. Prolonged or repeated contact may dry the skin resulting in skin irritation and dermatitis.

Ingestion: Moderately toxic. Swallowing large amounts may be harmful or fatal with central nervous system effects, which can include dizziness, loss of balance and coordination, unconsciousness, coma and even death.

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage. See section 2 for further details.

Eyes

Causes serious eye irritation.

Skin

May cause an allergic skin reaction. Causes skin irritation.

SECTION 5: Fire Fighting Measures

5.1 Extinguishing media

Water, carbon dioxide, foam or dry powder.

5.2 Special hazards arising from the substance or mixture

Hazardous decomposition: High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

Keep away from heat / sparks / open flames / hot surfaces - No smoking.

Keep cool.

Ground / bond container and receiving equipment.

Use explosion-proof electrical / ventilating / light / equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Avoid breathing dust / fume / gas / mist / vapors / spray.

Do not get in eyes, on skin, or on clothing.

5.3 Advice for fire-fighters

Do not mix with strong oxidizers such as liquid chlorine or concentrated oxygen.

Use water spray to cool non-involved containers.

Wear SCBA with full-face piece operating in a positive pressure demand mode and full protective gear.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Put on appropriate personal protective equipment (see section 8).

6.2 Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

6.3 Methods and material for containment and cleaning up

Shut off ignition sources including electrical equipment and flames. Contain spilled material. Absorb spills with inert material such as vermiculite, dry sand or earth. Place in a closed container but do not seal.

Ventilate area to remove vapors.

Disposal should be in accordance with local, state, and federal regulations. The preferred method of liquid waste is incineration. Cured, solid waste is considered non-hazardous and may be land filled if allowed.

Keep all waste from entering sewers, drains or waterways.

SECTION 7: Handling and Storage

7.1. Precautions for safe handling

Avoid prolonged or repeated skin contact. Avoid breathing aerosols, spray mists, and heated vapors. Use only in well ventilated area. Use good personal and industrial hygiene practices.

Keep container closed after each use.

See section 2 for further details. - [Prevention]:

7.2. Conditions for safe storage, including any incompatibilities

Handle containers carefully to prevent damage and spillage.

Incompatible materials: Contact with water will cause this product to cure. Incompatible with acids, bases, and oxidizers

Recommended storage range is less than 90°F.

See section 2 for further details. - [Storage]:

7.3 Specific end use(s)

No data available

SECTION 8: Exposure controls and personal protection

8.1. Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0001317-65-3	Calcium carbonate	OSHA	TWA 15 mg/m ³ (total) TWA 5 mg/m ³ (resp)
		ACGIH	TWA: 10 mg/m ³ Ceiling: 20 mg/m ³

		NIOSH	TWA 10 mg/m ³ (total) TWA 5 mg/m ³ (resp)
		Supplier	No Established Limit
0001330-20-7	Xylene	OSHA	STEL 150 ppm
		ACGIH	TWA: 100 ppm STEL: 150 ppm
		NIOSH	No Established Limit
		Supplier	No Established Limit
0009003-29-6	Polybutene	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0013463-67-7	Titanium dioxide	OSHA	TWA 15 mg/m ³
		ACGIH	TWA: 10 mg/m ³ 2B, Revised 2006,
		NIOSH	Footnote ca
		Supplier	No Established Limit
0026530-20-1	2-N-octyl-4-isothiazoline-3-one	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-16-1	Petroleum Resin	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0064742-49-0	Aliphatic Hydrocarbon	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0066070-58-4	BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE, HYD	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit
0068953-58-2	Alkyl quaternary ammonium bentonite	OSHA	No Established Limit
		ACGIH	No Established Limit
		NIOSH	No Established Limit
		Supplier	No Established Limit

Carcinogen Data

CAS No.	Ingredient	Source	Value
0001317-65-3	Calcium carbonate	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
0001330-20-7	Xylene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
		IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: Yes; Group 4: No;
0009003-29-6	Polybutene	OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

0013463-67-7	Titanium dioxide	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0026530-20-1	2-N-octyl-4-isothiazoline-3-one	IARC	Group 1: No; Group 2a: No; Group 2b: Yes; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0064742-16-1	Petroleum Resin	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0064742-49-0	Aliphatic Hydrocarbon	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0066070-58-4	BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE, HYD	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No
0068953-58-2	Alkyl quaternary ammonium bentonite	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		OSHA	Select Carcinogen: No
		NTP	Known: No; Suspected: No

8.2. Exposure controls

Respiratory

If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.

Eyes

Chemical splash goggles (ANSI Z-87.1 or approved equivalent) and/or face shield. Have an eye wash station available.

Skin

Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing. Wear impervious gloves.

Engineering Controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapor below occupational exposure limits suitable respiratory protection must be worn.

Other Work Practices

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details. – [Prevention]:

SECTION 9: Physical and chemical properties

Appearance

Viscous Liquid

Odor

Not specified

Odor threshold

Not determined

pH

Not available

Melting point / freezing point	Not applicable
Initial boiling point and boiling range	281 - 284°F
Flash Point	68°F
Evaporation rate (Ether = 1)	Slower than ether
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: 1% Upper Explosive Limit: 7%
Vapor pressure (Pa)	Not established
Vapor Density	Not available
Specific Gravity	Not available
Solubility in Water	Insoluble
Partition coefficient n-octanol/water (Log Kow)	Not Measured
Auto-ignition temperature	Not established
Decomposition temperature	Not available
Viscosity (cSt)	50,000 - 90,000 cps
VOC Content	less than 500 g/liter
Density	7.4 - 7.8 pounds per gallon
% Volatile	53 - 57% (by volume)

SECTION 10: Stability and reactivity

10.1. Reactivity

May polymerize

10.2. Chemical stability

Stable under normal circumstances.

10.3. Possibility of hazardous reactions

Reaction with water can create CO₂.

10.4. Conditions to avoid

Excessive heat and open flame.

10.5. Incompatible materials

Contact with water will cause this product to cure. Incompatible with acids, bases, and oxidizers

10.6. Hazardous decomposition products

High temperatures and fires may produce such toxic substances as carbon monoxide and carbon dioxide.

SECTION 11: Toxicological information

Acute toxicity

Exposure to solvent vapor concentrations from the component solvents in excess of the stated occupational exposure limits may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms include headache, nausea, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness.

Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin resulting in dryness, irritation and possible non-allergic contact dermatitis. Solvents may also be absorbed through the skin. Splashes of liquid in the eyes may cause irritation and soreness with possible reversible damage.

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation Vapor LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Aliphatic Hydrocarbon - (64742-49-0)	5,000.00, Rat - Category: 5	3,160.00, Rabbit - Category: 5	No data available	No data available	No data available
Petroleum Resin - (64742-16-1)	2,000.00, Mammal - Category: 4	No data available	No data available	No data available	No data available
Polybutene - (9003-29-6)	No data available	No data available	No data available	No data available	No data available

Titanium dioxide - (13463-67-7)	10,000.00, Rat - Category: NA	10,000.00, Rabbit - Category: NA	No data available	6.82, Rat - Category: NA	No data available
BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE, HYD - (66070-58-4)	No data available	No data available	No data available	No data available	No data available
Alkyl quaternary ammonium bentonite - (68953-58-2)	5,000.00, Rat - Category: 5	No data available	No data available	12.60, Rat - Category: NA	No data available
Calcium carbonate - (1317-65-3)	No data available	No data available	No data available	No data available	No data available
Xylene - (1330-20-7)	4,299.00, Rat - Category: 5	1,548.00, Rabbit - Category: 4	No data available	20.00, Rat - Category: NA	5,000.00, Rat - Category: 4
2-N-octyl-4-isothiazoline-3-one - (26530-20-1)	550.00, Rat - Category: 4	690.00, Rabbit - Category: 3	No data available	0.27, Rat - Category: 2	No data available

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	2	Causes skin irritation.
Serious eye damage/irritation	2	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	1	May cause an allergic skin reaction.
Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

SECTION 12: Ecological information

12.1. Toxicity

Toxic to aquatic life with long lasting effects.

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/l	48 hr EC50 crustacea, mg/l	ErC50 algae, mg/l
Aliphatic Hydrocarbon - (64742-49-0)	Not Available	2.60, Chaetogammarus marinus	Not Available

Petroleum Resin - (64742-16-1)	Not Available	Not Available	Not Available
Polybutene - (9003-29-6)	Not Available	Not Available	Not Available
Titanium dioxide - (13463-67-7)	1,000.00, Fundulus heteroclitus	5.50, Daphnia magna	5.83 (72 hr), Pseudokirchneriella subcapitata
BENZENE, ETHENYL-, POLYMER WITH 1,3-BUTADIENE, HYD - (66070-58-4)	Not Available	Not Available	Not Available
Alkyl quaternary ammonium bentonite - (68953-58-2)	Not Available	Not Available	Not Available
Calcium carbonate - (1317-65-3)	Not Available	Not Available	Not Available
Xylene - (1330-20-7)	3.30, Oncorhynchus mykiss	8.50, Palaemonetes pugio	100.00 (72 hr), Chlorococcales
2-N-octyl-4-isothiazoline-3-one - (26530-20-1)	0.0555, Oncorhynchus mykiss	0.18, Daphnia magna	0.084 (72 hr), Scenedesmus subspicatus

12.2. Persistence and degradability

There is no data available on the preparation itself.

12.3. Bioaccumulative potential

Not Measured

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

12.6. Other adverse effects

No data available.

SECTION 13: Disposal Considerations

13.1. Waste treatment methods

Observe all federal, state and local regulations when disposing of this substance.

SECTION 14: Transport Information

	DOT (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
14.1. UN number	UN1263	UN1263	UN1263
14.2. UN proper shipping name	UN1263, Paint, 3, III	Paint	Paint
14.3. Transport hazard class(es)	DOT Hazard Class: 3	IMDG: 3 Sub Class: Not Applicable	Air Class: 3
14.4. Packing group	III	III	III
14.5. Environmental hazards			
IMDG	Marine Pollutant: Yes (Aliphatic Hydrocarbon)		
14.6. Special precautions for user			
	No further information		

SECTION 15: Regulatory Information

Regulatory Overview	The regulatory data in Section 15 is not intended to be all-inclusive, only selected regulations are represented.
Toxic Substance Control Act (TSCA)	All components of this material are either listed or exempt from listing on the TSCA Inventory.
WHMIS Classification	B2 D2B
US EPA Tier II Hazards	Fire: Yes Sudden Release of Pressure: No Reactive: No Immediate (Acute): Yes Delayed (Chronic): No

EPCRA 311/312 Chemicals and RQs (lbs):

Xylene (100.00)

EPCRA 302 Extremely Hazardous:

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

EPCRA 313 Toxic Chemicals:

Ethyl Benzene

Xylene

Proposition 65 - Carcinogens (>0.0%):

Ethyl Benzene

Titanium dioxide

Proposition 65 - Developmental Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Female Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Proposition 65 - Male Repro Toxins (>0.0%):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

New Jersey RTK Substances (>1%):

Calcium carbonate

Titanium dioxide

Xylene

Pennsylvania RTK Substances (>1%):

Calcium carbonate

Titanium dioxide

Xylene

SECTION 16: Other information

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects

which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

H226 Flammable liquid and vapor.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H311 Toxic in contact with skin.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

H413 May cause long lasting harmful effects to aquatic life.

This is the first version in the GHS SDS format. Listings of changes from previous versions in other formats are not applicable.

This information is furnished without warranty, express or implied. This information is believed to be accurate to the best knowledge American WeatherStar. The information in this SDS relates only to the specific material designated herein. American WeatherStar assumes no legal responsibility for use of or reliance upon the information in this SDS.