



## Roof Surface/System Cross Reference Chart **CONCRETE**

SYSTEM	WARRANTY LENGTH	PRIMER	GAL/SQ	BASE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	TOP COAT	GAL/SQ	TOTAL DFT
<b>Urethane</b>	10 years	SBS Primer 950*	1	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aromatic Urethane 520	1.25	<b>38</b>
<b>Urethane (Hybrid)</b>	10 years	SBS Primer 950*	1	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aliphatic Urethane 510	1.25	<b>38</b>
	15 Years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—		Aliphatic Urethane 510	1.5	<b>45</b>
	20 Years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	Aliphatic Urethane 510	1.5	<b>55</b>
<b>Ure-A-Sil</b>	12 years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.1	<b>38</b>
										High-Solids Silicone 412	.9	
	15 years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.5	<b>45</b>
										High-Solids Silicone 412	1.1	
	20 years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.25	<b>55</b>
										High-Solids Silicone 412	.9	

Refer to application guidelines for detailed installation instructions. Adhesion tests are required for all roof restoration projects.

\* Depending on the condition of the existing roof system, a primer may not be necessary. Contact American WeatherStar technical services for more information.

DFT = Dry Film Thickness