

The coverage rates listed on this page are estimates based on typical conditions. It is critical to check all fasteners before adding mastic to ensure they are tight. Add stitch screws at seams before applying mastic when necessary. The width of the detail may need to be wider than estimated.



MATERIAL	COVERAGE/GALLON	WIDTH	WET MILS	AVERAGE DFT	COVERAGE/5 GALLON PAIL
----------	-----------------	-------	----------	-------------	------------------------

VERTICAL SEAMS

Silicone Brush-Grade 422	300 linear ft./gallon	2"	32	30	1500 linear ft./pail
Urethane Brush-Grade 522	200 linear ft./gallon	2"	35	25	1000 linear ft./pail

HORIZONTAL SEAMS, RAKES

Silicone Brush-Grade 422	150 linear ft./gallon	4"	32	30	750 linear ft./pail
Urethane Brush-Grade 522	100 linear ft./gallon	4"	45	30	500 linear ft./pail

FLASHINGS

Silicone Brush-Grade 422	50 linear ft./gallon	4"	64	60	250 linear ft./pail
Urethane Brush-Grade 522	35 linear ft./gallon	6"	90	60	175 linear ft./pail

FASTENERS

Silicone Brush-Grade 422, Urethane Brush-Grade 522	On average, a coverage rate of 1,000 sq. ft. per gallon on a standard R-panel metal roof will cover all fasteners.
-------------------------------------------------------	--------------------------------------------------------------------------------------------------------------------

