



Roof Surface/System Cross Reference Chart **CONCRETE**

SYSTEM	WARRANTY LENGTH	PRIMER	GAL/SQ	BASE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	TOP COAT	GAL/SQ	TOTAL DFT
Urethane	10 years	SBS Primer 950*	1	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aromatic Urethane 520	1.25	38
Urethane (Hybrid)	10 years	SBS Primer 950*	1	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aliphatic Urethane 510	1.25	38
	15 Years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—		Aliphatic Urethane 510	1.5	45
	20 Years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	Aliphatic Urethane 510	1.5	55
Ure-A-Sil	12 years	SBS Primer 950*	1	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—	—	Silicone 410	1.25	38
										High-Solids Silicone 412	.9	
	15 years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.5	45
										High-Solids Silicone 412	1.1	
	20 years	SBS Primer 950*	1	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	Silicone 410	1.25	Silicone 410	1.25	55
										High-Solids Silicone 412	1.8	
Ure-A-Sil California	12 years	SBS Primer 950*	1	Aromatic Urethane 512-CA	1.25	Aromatic Urethane 512-CA	1.25	—	—	High-Solids Silicone 412	.9	38
	15 years	SBS Primer 950*	1	Aromatic Urethane 512-CA	1.5	Aromatic Urethane 512-CA	1.5	—	—	High-Solids Silicone 412	1.1	45
	20 years	SBS Primer 950*	1	Aromatic Urethane 512-CA	1.5	Aromatic Urethane 512-CA	1.5	High-Solids Silicone 412	.9	High-Solids Silicone 412	.9	55

Refer to application guidelines for detailed installation instructions. Adhesion tests are required for all roof restoration projects.

* Depending on the condition of the existing roof system, a primer may not be necessary. Contact American WeatherStar technical services for more information.

DFT = Dry Film Thickness