



Roof Surface/System Cross Reference Chart
CONCRETE

SYSTEM	WARRANTY LENGTH	BASE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	INTERMEDIATE COAT	GAL/SQ	TOP COAT	GAL/SQ	TOTAL DFT
Urethane	10 years	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aromatic Urethane 520	1.25	38
Urethane (Hybrid)	10 years	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—		Aliphatic Urethane 510	1.25	38
	15 Years	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—		Aliphatic Urethane 510	1.5	45
	20 Years	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	Aliphatic Urethane 510	1.5	55
Ure-A-Sil	12 years	Aromatic Urethane 520	1.25	Aromatic Urethane 520	1.25	—	—	Silicone 410	1.25	38
								High-Solids Silicone 412	.9	
	15 years	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.5	45
								High-Solids Silicone 412	1.1	
	20 years	Aromatic Urethane 520	1.5	Aromatic Urethane 520	1.5	—	—	Silicone 410	1.25	55
								High-Solids Silicone 412	.9	

Refer to application guidelines for detailed installation instructions. Adhesion tests are required for all roof restoration projects.