



CLEAR PRIME 9000

DESCRIPTION

Clear Prime 9000 provides an excellent sealer for concrete or masonry surfaces. It will improve adhesion of coating systems and reduce excess usage of top coat materials allowing them to remain on the surface for maximum protection. The product has rapid drying water-based technology and is compatible with most types of top coats. It saves money by reducing absorption of top coats into substrate. Clear Prime 9000 has low VOC technology that meets most VOC regulations and is easy to apply.

ENVIRONMENTAL CONDITIONS

This product cures by water evaporation only. Product must not be applied when the ambient temperature is below 50°F or if there is any possibility it could fall below 32°F within 24 hours of application. Application is not recommended if rain or dew is likely to occur before product dries.

LIMITATIONS

Surface must be clean and dry. Do not apply over wet substrates or when inclement weather is imminent. Complete cure of Clear Prime 9000 requires complete evaporation of water. Cool temperatures and high humidity retard cure.

WARRANTY

American WeatherStar warrants that the material supplied will meet or exceed physical properties as published. The contractor guarantees that workmanship will be free of defects in coating application. Since performance of previously installed substrate is beyond the control of American WeatherStar or the contractor, requests for additional warranty coverage shall be subject to prior approval by American WeatherStar.

APPLICATION TEMPERATURES

Min Ambient: 50°F (10°C)
 Max Ambient: 110°F (43.3°C)
 Min Surface: 50°F (10°C)
 Max Surface: 130°F (54.4°C)

Minimum temperatures must be rising following applications. Contact technical services for more information.

Do not apply when:

- Dew point is within 5°F (2.77°C) of ambient temperatures
- Precipitation, fog, or dew is imminent prior to cure of the product
- Freezing temperatures are expected prior to cure of the product

TECHNICAL DATA

SOLIDS BY VOLUME:	25% ± 2%
WEIGHT:	8.6 lbs per gallon ± 0.2
VOC:	100 g/liter
MINIMUM APPLICATION TEMP.:	50°F
DRY TIME:	1-4 hours
SERVICE TEMP. RANGE:	-40° to 200°F
SHELF LIFE:	12 months
CLEAN UP:	Water
COLOR:	Clear
PACKAGING:	5 gallon

SAFETY INFORMATION

Read the Safety Data Sheet (SDS) and container labels for detailed health and safety information. This product is intended for industrial use by properly trained professional applicators only.

AMERICAN WEATHERSTAR LLC

8095 Padgett Switch Rd. | Irvington, AL 36544 | USA
www.americanweatherstar.com | info@americanweatherstar.com
 Toll Free: 800-771-6643 | Fax: 251-479-3602